

IN THE CLAIMS:

Please cancel claims 5-7, 12-14, 16, and 18; and add new claims 19-21 as follows:

1. (Previously amended) A buffer management system comprising:

Sub E1
a buffer pool further comprised of an amount of fixed storage and an amount of virtual storage;

a target maximum fixed value for the amount of fixed storage, the target maximum fixed value dynamically alterable by a system administrator;

a target maximum virtual value for the amount of virtual storage, the target maximum virtual value dynamically alterable by a system administrator; and

a buffer manager for dynamically varying the amount of fixed storage and the amount of virtual storage based on a comparison of present usage of the amount of fixed storage and the amount of virtual storage to target maximum fixed and target maximum virtual values.

2. (Original) The buffer management system of claim 1, wherein the buffer pool is further comprised of fixed, pageable and released logical partitions and each of the buffers in the buffer pool resides in a state comprising one of said logical partitions.

3. (Original) The buffer management system according to claim 2, further comprising a buffer index table further comprising buffer index elements wherein each entry represents one buffer in the buffer pool.

4. (Original) The buffer management system according to claim 3, wherein said buffer index elements further comprise a buffer state information field which represents the logical partition where the buffer resides and a pointer field to the next available buffer in the same state within the buffer pool.

5.-7. (Canceled)

8. (Previously amended) An article of manufacture comprising:

 a buffer pool further comprised of an amount of fixed storage and an amount of virtual storage;

 a target maximum fixed value for the amount of fixed storage, the target maximum fixed value dynamically alterable by a system administrator;

 a target maximum virtual value for the amount of virtual storage, the target maximum virtual value dynamically alterable by a system administrator; and

 a buffer manager for dynamically varying the amount of fixed storage and the amount of virtual storage based on a comparison of present usage of the amount of fixed storage and the amount of virtual storage to target maximum fixed and target maximum virtual values.

9. (Original) The article of manufacture according to claim 8, wherein the buffer pool is further comprised of fixed, pageable and released logical partitions.

10. (Original) The article of manufacture according to claim 9, further comprising a buffer index table further comprising buffer index elements wherein each entry represents one buffer in the buffer pool.

11. (Original) The article of manufacture according to claim 10, wherein said buffer index elements further comprise a buffer state information field which represents the logical partition where the buffer resides and a pointer field to the next available buffer in the same state within the buffer pool.

12.-14. (Canceled)

15. (Previously Added) The buffer management system of claim 1, further comprising means for testing whether a buffer resides in physical memory.

16. (Cancelled)

17. (Previously Added) The article of manufacture of claim 8, further comprising means for testing whether a buffer resides in physical memory.

18. (Canceled)

19. (New) The buffer management system of claim 1, further comprising a comparator configured to compare present usage of the amount of fixed storage and present usage of the amount of virtual storage to the target maximum fixed value and the target maximum virtual value.

20. (New) The buffer management system of claim 1, wherein the fixed storage is configured for memory paging and the virtual storage is configured for memory paging.

21. (New) The buffer management system of claim 2, wherein the buffer manager is further configured to dynamically vary the amount of fixed storage and the amount of virtual storage by moving buffers in the buffer pool between the logical partitions.